

ELEVATIONS : FINISH FLOOR LEVEL ↓				
DR / WD NO.	D1			
DESCRIPTION :	40MM THICK OPENABLE ALUMINUM FRAMED DOOR PANEL			
FRAME :	120MM ALUMINUM FRAME			
HARDWARE :	DOOR CLOSER CYLINDRICAL LOCK BUTT HINGE STOPPER HOLDER KICKER			
GLAZING :	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED			
	D2			
	40MM THICK OPENABLE TIMBER FRAMED DOOR PANEL			
	120MM TIMBERFRAME			
	DOOR CLOSER CYLINDRICAL LOCK BUTT HINGE STOPPER HOLDER KICKER			
	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED			
	D3			
	40MM THICK OPENABLE ALUMINUM FRAMED DOOR PANEL			
	120MM FRAME			
	DOOR CLOSER CYLINDRICAL LOCK BUTT HINGE STOPPER HOLDER			
	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED			
	D4			
	40MM THICK OPENABLE TIMBER FRAMED DOOR PANEL			
	120MM TIMBERFRAME			
	DOOR CLOSER CYLINDRICAL LOCK BUTT HINGE STOPPER HOLDER			
	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED			
	D5			
	40MM THICK OPENABLE TIMBER FRAMED DOOR PANEL			
	120MM TIMBERFRAME			
	DOOR HANDLE BUTT HINGE			
	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED			

DOOR SCHEDULE

SCALE 1:50

GENERAL NOTE FOR THE INSTALLATION OF DOORS:

ENSURE THAT ALL OPENING EXTERNAL BUILDING PERIMETER DOORS ARE LOCKABLE.
 – PERIMETER DOORS SHOULD MEET THE FOLLOWING BUILDING DESIGN STANDARDS:
 – BE FITTED WITH A QUALITY LOCKSET THAT COMPLES WITH FIRE REGULATIONS.