



DETAILS OF MS PLATE



DETAILS OF LIFTING HOOK




DETAILS OF STEPS

INTERNAL DIMENSIONS OF GATE VALVE CHAMBERS :

VALVE DIA.(mm)	L (mm)	B (mm)
Upto 200	1000	1000
250 / 300	1500	1500

NOTES

1. ALL DIMENSIONS ARE IN MILLIMETRES
2. CONCRETE PROTECTION TO BE AS SPECIFIED
3. THE SEALANT SHALL BE ELASTIC, ONE COMPONENT, GUN APPLIED SEALANT ON POLYURETHANE BASIS CONFORMING TO BS 4254 SUITABLE FOR METAL WORK AND CONCRETE.
Eg. SIKAFLEX - 1A OR APPROVED EQUAL.
4. MANHOLE FRAME SHALL BE FIRMLY FIXED TO THE CHAMBER WITH 4 Nos. RAG BOLTS OR SIMILAR MANNER.
5. MANHOLE COVER SHALL BE OF HINGED, HEAVY DUTY (CLASS D 400) VENTILATED TYPE WITH 600 DIA. MINIMUM CLEAR OPENING.



GREENTECH CONSULTANTS (Pvt.) Ltd IN ASSOCIATION WITH
DEVELOPMENT COLLABORATION PARTNERSHIP (Pvt.) Ltd MALDIVES
AND OPTIMUM SOLOUTIONS (Pvt) Ltd, MALDIVES

CONSULTANCY SERVICES FOR DESIGN OF WATER SUPPLY FACILITIES IN Ha.HORAFUSHI,
Hdh.HANIMAADHOO,Sh.MILANDHOO,R.UNGOOFARU,Lh.NAIFARU,Dh,KUDAHUVADHOO
,Th.GURADHOO AND Ga.VILLINGILI , MALDIVES

TITLE:

GATE VALVE CHAMBERS
DISTRIBUTION NETWORK
R.UNGOOFAARU

DESIGN

ENGINE

	DATE
--	------

DRAWN

ER

CHECKED

DESIGN CHIEF

LINGOOFAARI/STD/04

APPROVED

■

STD/04

SL.NO

--	--

DRWIN

--	--

--	--

DESCRIPTION
