




W1a	FIXED WITH AWNING-TYPE WINDOW
REMARKS	WHITE POWDER COATED ALUMINUM -FRAMED 6MM THK. TINTED GLASS WINDOW PANEL
LOCATION	IMAAM AREA
QUANTITY	1 NO
OPEN AREA	0.58




W4	ALUMINUM LOUVERS
REMARKS	WHITE POWDER COATED ALUMINUM-FRAMED WINDOW WITH FIXED GLASS
LOCATION	CEILING VENT
QUANTITY	24 NOS
OPEN AREA	0.38 SQM.



W2	ALUMINUM FIX DOOR
REMARKS	WHITE POWDER COATED ALUMINUM -FRAMED 6MM THK. TINTED GLASS WINDOW PANEL
LOCATION	FACADE ENTRY
QUANTITY	2 NOS
OPEN AREA	0.55 SQM.




W5	AWNING-TYPE WINDOW
REMARKS	WHITE POWDER COATED ALUMINUM -FRAMED 6MM THK. TINTED GLASS WINDOW PANEL
LOCATION	MALE/FEMALE TOILET (ABLUTION AREA)
QUANTITY	2 NOS
OPEN AREA	0.35 SQM.



W6	ALUMINUM CASEMENT WINDOW
REMARKS	WHITE POWDER COATED ALUMINUM-FRAMED WINDOW WITH AL LOUVERS
LOCATION	FEMALE ABLUTION AREA
QUANTITY	1 NO
OPEN AREA	1.49 SQM.

DOORS & WINDOWS SCHEDULE



NOTE:-
-ALL DOORS & WINDOWS TO BE CHECKED ON SITE BEFORE FABRICATION.
-ALL DOOR & WINDOWS VIEWED FROM EXTERIOR, FOR DOOR SWING, REFER TO FLOOR PLANS.
-THE DOORS / WINDOWS WHICH DOES NOT TOUCH THE BEAM PLEASE PUT A LINTEL BEAM (LB) ABOVE THE DOOR / WINDOW.

LEGEND:-
ST - SOLID TIMBER
AL - ALUMINIUM LOUVERS
FG - FRITTED GLASS
FTG - FIXED TINTED GLASS
TG - TINTED GLASS
OPG - OPAQUE GLASS
TG - TINTED GLASS
FTG - FIXED TINTED GLASS